

**Hybrid and Multi Material Additive Manufacturing for Aerospace and Solar Thermal Management Systems: Materials, Processes, Design Innovations, and Emerging Challenges**Dr. Sagar S. Gaddamwar<sup>1</sup>, Dr. Rahul M. Sherekar<sup>2</sup>, Prof. Prasanjeet H. Bhagat<sup>3</sup><sup>1,2</sup> Mechanical Engineering Department, Jawaharlal Darda Institute of Engineering and Technology, Yavatmal, Maharashtra, India<sup>3</sup> Government Polytechnic, Yavatmal, Maharashtra, India<sup>1</sup>sagar\_gaddamwar@jdiet.ac.in<sup>2</sup>rahul\_sherekar@jdiet.ac.in**Abstract**

Thermal management plays a critical role in aerospace platforms and solar thermal energy systems where high heat fluxes, compact design requirements, and strict weight constraints challenge conventional manufacturing methods. Traditional fabrication techniques such as machining, casting, and brazing often restrict geometric complexity and limit thermal performance. Hybrid and multi material additive manufacturing (AM) has recently emerged as a transformative approach capable of producing highly integrated thermal components with complex internal geometries and spatially tailored material properties.

This study presents a critical and comparative review of hybrid and multi material additive manufacturing technologies applied to aerospace and solar thermal management systems. Unlike existing review studies that mainly summarize additive manufacturing processes, the present work provides a comparative evaluation of process capabilities, material compatibility, and thermal performance characteristics of additively manufactured heat exchangers and solar thermal receivers. Furthermore, the study analyzes design innovations such as topology optimized heat exchangers, lattice structures, conformal cooling channels, and functionally graded materials. A comparison between conventional manufacturing and hybrid AM based thermal systems indicates significant improvements in heat transfer performance, weight reduction, and structural integration. However, challenges related to material qualification, multi material bonding, residual stresses, and certification standards remain barriers to widespread industrial adoption. The paper also discusses emerging research directions including digital twin integration, artificial intelligence assisted design optimization, and smart thermal components.

The findings demonstrate that hybrid and multi material additive manufacturing has the potential to significantly enhance the performance and efficiency of next generation aerospace and solar thermal management systems.

**Keywords:** Additive Manufacturing (AM); Aerospace Thermal Management; Solar Thermal Systems; Heat Exchangers; Functionally Graded Materials; Topology optimization.

**1. Introduction:** Efficient thermal management is essential for the safe operation of modern aerospace systems and solar thermal energy technologies. Aircraft engines, avionics systems, spacecraft electronics, and satellite power systems generate substantial heat during operation. Similarly, solar thermal systems such as concentrated solar power receivers and solar collectors operate under high and often non uniform heat flux conditions.

Traditional manufacturing techniques such as machining, brazing, and casting impose several limitations on the design of thermal components. These methods often restrict the fabrication of complex internal channels and lightweight structures required for high performance heat exchangers. As a result, conventional thermal management components typically involve multi part assemblies, increased weight, and limited heat transfer efficiency. Additive manufacturing enables layer wise fabrication of components with complex geometries, integrated cooling channels, and optimized internal structures. Hybrid additive manufacturing combines additive processes with subtractive machining to improve dimensional accuracy and surface quality. Multi material additive manufacturing further enables spatial variation of material properties, which is particularly beneficial for thermal systems exposed to large temperature gradients.

**Key Contributions of This Study:** The main contributions of this work are:

1. A comparative analysis of hybrid and multi material additive manufacturing processes for aerospace and solar thermal applications.
2. A performance comparison between conventional manufacturing and AM based thermal systems.
3. Evaluation of material selection strategies for high temperature thermal management systems.
4. Identification of design innovations such as topology optimization, lattice architectures, and conformal cooling channels.
5. Discussion of current manufacturing challenges, certification requirements, and future research opportunities.

**2. Literature Review:** Additive manufacturing (AM) has rapidly evolved as a transformative manufacturing technology capable of producing complex components with improved functional performance. In thermal management systems, particularly those used in aerospace and energy applications, AM enables the fabrication of intricate internal geometries, optimized flow channels, and lightweight structures that are difficult or impossible to achieve through conventional manufacturing processes. These advantages have led to increasing research interest in the application of AM technologies for the development of advanced heat exchangers, thermal receivers, and integrated cooling systems. Recent studies have extensively explored the application of additive manufacturing for aerospace heat exchangers. Careri et al. [1] conducted a comprehensive review on the use of additive manufacturing in aerospace heat exchanger applications. Their analysis highlighted the ability of metal AM processes such as laser powder bed fusion (LPBF) to fabricate compact heat exchangers with highly complex internal channel configurations. The study demonstrated that additively manufactured heat exchangers can achieve significantly higher surface-area-to-volume ratios compared with conventionally manufactured units, thereby improving heat transfer efficiency. However, the authors also emphasized challenges related to surface roughness, manufacturing defects, and process reliability that may affect the thermal and mechanical performance of such components.

The development of multi material additive manufacturing has further expanded the design possibilities for thermal management systems. Saltzman et al. [2] investigated emerging trends in multi material AM for aerospace thermal systems and highlighted the potential advantages of integrating different materials within a single component. By combining materials with varying thermal conductivity and mechanical properties, multi-material AM enables the fabrication of functionally graded structures capable of withstanding high temperature gradients and thermal stresses. Their study also identified several technical challenges associated with multi material processing, including interfacial bonding, material compatibility, and process control.

Hybrid manufacturing approaches, which integrate additive manufacturing with conventional subtractive machining processes, have been proposed to overcome some of the limitations associated with standalone AM technologies. Li et al. [3] analyzed hybrid additive subtractive manufacturing systems from both thermal and structural perspectives. Their research demonstrated that the integration of in situ machining operations during additive manufacturing improves dimensional accuracy and surface finish, which are critical requirements for aerospace components. Hybrid manufacturing also allows the production of complex geometries while maintaining the precision required for high-performance thermal systems.

Several studies have also focused on optimizing heat exchanger geometries through additive manufacturing techniques. Zhang and Fang [4] investigated the hybrid fabrication of aerospace heat exchangers using LPBF combined with CNC machining. Their results showed that optimized internal channel designs produced through additive manufacturing significantly improved thermal performance while reducing pressure losses within the system. The study emphasized those additive manufacturing offers greater design flexibility compared with traditional fabrication techniques, enabling the development of highly efficient thermal management components.

The concept of functionally graded materials (FGMs) has also gained attention in the context of multi-material additive manufacturing. Liu et al. [5] explored the fabrication of graded metal and ceramic structures for aerospace applications. Their findings indicated that functionally graded materials can effectively manage thermal stresses and enhance the durability of components operating under extreme thermal conditions. The ability to gradually vary material composition across a component allows designers to tailor thermal conductivity and mechanical strength according to specific operational requirements.

The broader technological development of additive manufacturing has been documented in several key studies. Bourell et al. [6] presented a comprehensive roadmap outlining the future directions of additive manufacturing technologies, including materials development, process improvements, and industrial applications. Their work emphasized the importance of continued research in process optimization, material qualification, and standardization to support large scale industrial adoption of AM technologies.

Design methodologies specifically tailored for additive manufacturing have also been investigated extensively. Thompson et al. [7] discussed design for additive manufacturing (DFAM) principles and highlighted the opportunities provided by AM technologies for producing lightweight and high-performance components. The authors emphasized that topology optimization, lattice structures, and internal channel networks are key design strategies that enable significant improvements in mechanical and thermal performance. In the context of lattice structures, Rafi et al. [8] conducted a parametric investigation of the mechanical and thermal properties of LPBF-produced lattice architectures. Their study demonstrated that lattice structures significantly increase the surface area available

for heat transfer while reducing the overall weight of the component. These characteristics make lattice-based structures particularly attractive for advanced heat exchangers and thermal management systems.

Despite the numerous advantages of additive manufacturing, quality assurance and reliability remain important challenges for industrial applications. Cunningham and Deckard [9] reviewed non destructive evaluation techniques used for inspecting metal additively manufactured components. Their work highlighted that defects such as porosity, lack of fusion, and residual stresses can significantly affect the structural integrity and thermal performance of AM components. Consequently, advanced inspection techniques such as computed tomography and ultrasonic testing are essential for ensuring component reliability. Additive manufacturing has also demonstrated promising potential in industrial heat exchanger applications beyond aerospace systems. Kakad and Gaddamwar [10] investigated the optimization of heat exchanger designs for textile industry applications using additive manufacturing technologies. Their empirical study indicated that AM based heat exchanger designs can improve energy efficiency while simplifying manufacturing processes.

Foundational studies on additive manufacturing technologies have also contributed significantly to the understanding of AM processes and materials. Gibson et al. [11] provided a comprehensive overview of additive manufacturing technologies, including various 3D printing processes, material systems, and industrial applications. Their work remains an important reference for understanding the technological principles and capabilities of additive manufacturing.

Similarly, Ngo et al. [12] presented a detailed review of additive manufacturing processes, materials, and applications across multiple industries. Their study highlighted the rapid advancement of AM technologies and identified key challenges related to material development, process control, and scalability.

In addition to aerospace and industrial applications, additive manufacturing has also been explored in the context of renewable energy systems. Gaddamwar and Sherekar [13] investigated solar chimney power plant systems from a thermodynamic perspective and emphasized the importance of efficient thermal management in renewable energy technologies. Their work indicates that advanced manufacturing techniques such as AM could potentially improve the design and efficiency of energy systems involving complex thermal interactions. Further advancements in additive manufacturing applications for industrial engineering systems have been discussed by Kakad and Gaddamwar [14], who examined opportunities and challenges associated with integrating AM technologies into textile engineering applications. Their study highlighted that additive manufacturing offers new possibilities for optimizing component design, improving energy efficiency, and reducing manufacturing complexity. Although significant progress has been made in the development of additive manufacturing technologies and their applications in thermal management systems, existing studies often focus on individual aspects such as process development, material innovation, or specific industrial applications. Comprehensive studies that simultaneously evaluate hybrid additive manufacturing, multi-material fabrication strategies, and advanced design methodologies for aerospace and solar thermal systems remain relatively limited.

Therefore, the present study aims to address this gap by providing a systematic evaluation of hybrid and multi-material additive manufacturing technologies for aerospace and solar thermal management systems, with particular emphasis on materials, design innovations, and emerging research challenges.

**3. Applications of Hybrid and Multi Material Additive Manufacturing:** Hybrid additive manufacturing integrates layer wise material deposition processes with conventional subtractive machining techniques to achieve both geometric complexity and high dimensional accuracy. This manufacturing approach is particularly advantageous for thermal management systems used in aerospace and solar energy applications, where components must simultaneously satisfy strict requirements related to weight, thermal efficiency, and structural integrity. Multi material additive manufacturing further extends these capabilities by enabling the fabrication of components composed of different materials with tailored thermal and mechanical properties.



**Figure 1 Hybrid and Multi Material Additive Manufacturing for Solar Aerospace Thermal management Systems**

The schematic representation shown in Figure 1 illustrates the conceptual framework of hybrid and multi material additive manufacturing applied to aerospace and solar thermal management systems. The figure highlights the integration of advanced additive manufacturing technologies, including laser powder bed fusion, directed energy deposition, and hybrid additive subtractive manufacturing processes, with multi material design strategies. These technologies enable the production of complex thermal components such as compact heat exchangers, conformal cooling channels, and high efficiency solar absorbers. As depicted in Figure 1, hybrid manufacturing combines additive material deposition with precision machining operations to achieve improved surface finish and dimensional control. This integration allows engineers to fabricate components with intricate internal geometries while maintaining the tight tolerances required for aerospace systems. The ability to integrate multiple manufacturing processes within a single production workflow significantly enhances the functional performance of thermal management devices. The figure also demonstrates the role of multi material additive manufacturing in improving thermal performance. By selectively depositing materials with different thermal conductivities and mechanical characteristics, engineers can create functionally graded structures that effectively manage heat transfer and thermal stresses. For example, high thermal conductivity materials such as copper alloys may be used in regions requiring rapid heat dissipation, while high temperature resistant materials such as nickel based superalloys can be applied in areas exposed to extreme thermal loads. In solar thermal applications, hybrid and multi material additive manufacturing enables the development of advanced absorber plates, solar receivers, and thermal storage components with optimized internal flow structures. These designs improve heat absorption and energy transfer efficiency while reducing overall system weight. Similarly, in aerospace applications, additively manufactured heat exchangers and cooling systems can significantly enhance the thermal management capabilities of aircraft engines, avionics systems, and spacecraft electronics. Overall, Figure 1 illustrates how the integration of hybrid additive manufacturing processes and multi material fabrication techniques provides a powerful platform for developing next generation thermal management systems. The combination of advanced manufacturing technologies and optimized material distribution enables the production of high performance thermal components with improved efficiency, reliability, and design flexibility.

**Table No.1: Applications of Hybrid and Multi Material Additive Manufacturing**

AM Process	Aerospace Applications	Solar Applications
LPBF+CNC Milling	High Precision Heat Exchangers	Functionally graded solar absorbers
Laser DED + CNC Machining	Repair and customization of thermal components	Multi material receivers for CSP
WAAM + Machining	Large scale cold plates, structural supports	Lightweight supports for solar towers

Table I summarizes the key hybrid and multi material additive manufacturing processes and their representative applications in aerospace and solar thermal systems. The integration of LPBF with CNC milling enables the fabrication of high precision aerospace heat exchangers with complex internal channels, while also supporting functionally graded solar absorber components. Laser directed energy deposition combined with machining is particularly effective for repair, customization, and multi material integration in thermal components, making it suitable for advanced concentrated solar power (CSP) receivers. Wire arc additive manufacturing followed by machining is well suited for large scale structures, offering a cost effective solution for aerospace cold plates and lightweight structural supports in solar tower applications.

**4. Materials for Thermal Management Systems**

Material selection strongly influences the performance of thermal management systems. High thermal conductivity, corrosion resistance, and mechanical strength are important factors when selecting materials for aerospace and solar applications.

Table II presents commonly used materials and their thermal properties relevant to thermal management applications.

**Table No.II: Materials for Advanced Thermal Management**

Material	Density	Thermal Conductivity	Aerospace	Solar Applications
Aluminum Alloys	4.5-8.2	82-43	Lightweight heat enhancement	Yes
Copper Alloys	3.1-5.8	55-209	High Heat	Yes
Nickel based Super Alloys	3.0-7.3	390-126	High thermal receivers for CS	Yes
Cements	6.3-8	85-90	Comfort SSF materials	Yes
Silicon Carbide	1.5-4.7	85-95	High thermal stability	Yes

Table II presents representative material classes commonly explored for advanced thermal management applications in aerospace and solar energy systems. Aluminum alloys are preferred for lightweight heat transfer components due to their favorable balance of density and thermal conductivity. Copper alloys offer superior heat dissipation capability and are therefore employed in high heat flux regions such as cold plates and solar receivers. Nickel based superalloys are used in extreme thermal environments where high temperature strength and oxidation resistance are critical. Cement based and silicon carbide materials provide thermal stability and durability, making them suitable for solar structural and thermal storage functions. The selection of these materials is strongly influenced by operating temperature, thermal performance requirements, and compatibility with additive manufacturing processes.

**Table No. III: Materials and thermal properties relevant to additively manufactured heat exchangers and solar thermal receivers**

Material	Density (kg·m <sup>-3</sup> )	Thermal Conductivity (W·m <sup>-1</sup> ·K <sup>-1</sup> )	Maximum Service Temperature (°C)	Relevance to Aerospace & Solar Applications
AlSi10Mg	2650-2700	150-170	~300	Lightweight, high thermal conductivity; widely used in LPBF fabricated aerospace heat exchangers and low-to-moderate temperature solar absorbers
CuCrZr	8800-8950	320-340	~500	Excellent heat dissipation; suitable for high heat flux solar receivers and compact cold plates
Pure Copper (AM grade)	~8960	360-390	~450	Ultra-high thermal conductivity for advanced thermal management, limited by oxidation and manufacturability
Ti-6Al-4V	4400-4450	6-8	~400	High strength to weight ratio; structural thermal components in aerospace with integrated cooling
Ceramic Metal FGMs	Variable	Tailored (10-300)	>800	Functionally graded thermal behavior; ideal for solar receivers with high thermal gradients
SiC-based Composites	3100-3200	85-120	>1000	High thermal stability and radiation resistance; advanced solar and aerospace thermal protection systems

Table III provides a comparative overview of key materials and their thermal properties relevant to additively manufactured heat exchangers and solar thermal receivers. Aluminum alloy AlSi10Mg is widely adopted for lightweight thermal components operating at moderate temperatures, while copper based materials such as CuCrZr and additively manufactured pure copper are preferred for high heat-flux applications due to their superior thermal conductivity. Titanium alloy Ti-6Al-4V offers an excellent balance between mechanical strength and thermal performance, making it suitable for structurally integrated cooling systems in aerospace applications. Ceramic metal functionally graded materials enable tailored thermal and mechanical behavior, which is particularly advantageous for solar receivers exposed to severe thermal gradients. SiC based composites exhibit exceptional thermal stability and high temperature capability, positioning them as promising candidates for advanced solar and aerospace thermal protection and heat management systems.

**5. Hybrid and Multi Material Additive Manufacturing Technologies**

**5.1 Hybrid Additive Manufacturing:** Hybrid additive manufacturing integrates material deposition with precision machining in a single or sequential manufacturing workflow. This approach is particularly beneficial for thermal management components that require complex internal geometries along with tight dimensional tolerances and smooth heat transfer surfaces. Common hybrid configurations include laser powder bed fusion combined with CNC machining, directed energy deposition with in situ milling, and wire arc additive manufacturing followed by finish machining.

For aerospace heat exchangers and solar receiver plates, hybrid AM enables accurate control of channel dimensions, improved surface integrity, and enhanced thermal contact at interfaces. Additionally, hybrid approaches reduce post processing requirements and improve overall manufacturing efficiency.

**5.2 Multi Material and Functionally Graded Manufacturing:** Multi material additive manufacturing enables the fabrication of components with location specific material properties within a single build. Functionally graded materials (FGMs) are particularly advantageous in thermal systems where regions exposed to high heat flux demand high thermal conductivity, while other regions prioritize mechanical strength or weight reduction. Directed energy deposition and powder composition modulation in laser powder bed fusion are among the most effective techniques for producing graded metallic and metal ceramic structures.

**6. Materials for Aerospace and Solar Thermal Management Systems:** Material selection plays a critical role in determining the thermal efficiency, structural integrity, and service life of AM fabricated thermal components. Aluminum alloys such as AlSi10Mg are widely used due to their low density and favorable thermal conductivity, making them suitable for lightweight aerospace heat exchangers and solar collector plates. Copper and copper based alloys, including CuCrZr, offer superior thermal conductivity and are preferred for high heat flux applications such as solar receivers and cold plates, despite processing challenges in powder bed systems. Titanium alloys provide excellent strength to weight ratios and corrosion resistance, making them suitable for aerospace thermal structures operating under moderate thermal loads. Nickel based superalloys are employed in extreme temperature environments where oxidation resistance and mechanical stability are critical. Ceramic metal composites and graded material systems further expand design possibilities by combining thermal insulation with structural support.

**7. Advanced Design Strategies for Additive Manufacturing:** Additive manufacturing enables innovative thermal component designs that are difficult to achieve using conventional manufacturing techniques.

**7.1 Topology Optimized Heat Exchangers:** Topology optimization is widely used in additive manufacturing to minimize weight while maximizing heat transfer efficiency. Thompson et al. [9] demonstrated that topology optimized structures can significantly improve thermal performance compared with traditional heat exchanger designs.

**7.2 Lattice Structures:** Lattice structures fabricated using additive manufacturing provide high surface-area-to-volume ratios, which enhance convective heat transfer. Rafi et al. [11] reported that lattice architectures significantly improve heat transfer efficiency while reducing component weight.

**7.3 Conformal Cooling Channels:** Conformal cooling channels follow the geometry of the component and allow uniform heat removal. Such cooling networks are widely used in aerospace heat exchangers and solar thermal receivers.

**8. Comparison with State of the Art Methods**

A comparison between conventional manufacturing and additive manufacturing approaches highlights the advantages of hybrid AM.

**Table IV: Comparison between Conventional Manufacturing and Additive Manufacturing**

Parameter	Conventional Manufacturing	Hybrid AM
Geometric Complexity	Limited	Very High
Part Integration	Multi-component	Single integrated structure
Heat Transfer Efficiency	Moderate	High
Weight	Higher	Lower
Manufacturing Flexibility	Low	High

Table IV shows comparison demonstrates that additive manufacturing enables improved thermal performance through optimized internal geometries and reduced structural weight.

**9. Manufacturing Challenges and Quality Assurance:** Despite its advantages, additive manufacturing faces several technical challenges. Residual stresses, porosity formation, and surface roughness may affect thermal conductivity and structural reliability. Advanced non destructive evaluation techniques such as X-ray computed tomography and ultrasonic inspection are widely used to ensure quality control in additively manufactured components [12].

**10. Sustainability and Certification Considerations:** Additive manufacturing contributes to sustainability by reducing material waste and enabling part consolidation. Gibson et al. [14] emphasized that AM technologies can reduce manufacturing energy consumption and material usage.

However, aerospace applications require strict certification procedures including ASTM standards and AS9100 quality management systems.

#### 11. Future Research Directions

Future research in hybrid additive manufacturing is expected to focus on several emerging areas including:

- AI based design optimization
- Digital twin technology for thermal systems
- Smart thermal components with embedded sensors
- Advanced multi-material interfaces
- High conductivity AM materials

#### 9. Conclusion

This study presented a comprehensive comparative review of hybrid and multi material additive manufacturing technologies for aerospace and solar thermal management systems. The analysis demonstrated that additive manufacturing enables significant improvements in thermal performance, structural integration, and weight reduction compared with conventional manufacturing techniques. Advanced design strategies such as topology optimization, lattice architectures, and conformal cooling channels further enhance heat transfer efficiency.

However, challenges related to material qualification, multi material bonding, residual stresses, and certification standards remain key barriers to large scale industrial implementation.

Continued advancements in process control, digital design frameworks, and material development are expected to further accelerate the adoption of additive manufacturing in aerospace and solar thermal technologies.

#### References

- [1] Careri, F., Khan, R.H.U., Todd, C., Attallah, M.M., 2023. Additive manufacturing of heat exchangers in aerospace applications: A review. *Applied Thermal Engineering*, 235, 121387. <https://doi.org/10.1016/j.applthermaleng.2023.121387>
- [2] Saltzman, D., Bichnevicius, M., Lynch, S., Simpson, T.W., Reutzel, E.W., Dickman, C., Martukanitz, R.P., 2023. Multi-material additive manufacturing for aerospace thermal systems: Trends and challenges. *Journal of Materials Processing Technology*, 317, 117877. <https://doi.org/10.1016/j.jmatprotec.2023.117877>
- [3] Li, X., Zhou, Y., Chen, H., 2022. Hybrid additive-subtractive manufacturing in aerospace: Thermal and structural perspectives. *Additive Manufacturing*, 55, 102955. <https://doi.org/10.1016/j.addma.2022.102955>
- [4] Zhang, T., Fang, H., 2021. Hybrid LPBF-CNC fabrication of aerospace heat exchangers: Process optimization and thermal performance. *Progress in Additive Manufacturing*, 6(4), 323–338. <https://doi.org/10.1007/s40964-020-00182-5>
- [5] Liu, P., Zhang, J., Li, W., 2020. Functionally graded materials in multi-material additive manufacturing: Aerospace applications. *Journal of Alloys and Compounds*, 824, 153997. <https://doi.org/10.1016/j.jallcom.2020.153997>
- [6] Bourell, D., Leu, M., Rosen, D., 2017. Roadmap for additive manufacturing: Materials, processes, and applications. *JOM*, 69(3), 557–572. <https://doi.org/10.1007/s11837-016-2190-8>
- [7] Thompson, M.K., Moroni, G., Vaneker, T., et al., 2016. Design for additive manufacturing: Trends, opportunities, considerations, and constraints. *CIRP Annals*, 65(2), 737–760. <https://doi.org/10.1016/j.cirp.2016.05.004>
- [8] Rafi, K., Starr, T., Stucker, B., 2013. Parametric study of mechanical and thermal properties of LPBF lattice structures. *Rapid Prototyping Journal*, 19(5), 353–364. <https://doi.org/10.1108/RPJ-12-2011-0122>
- [9] Cunningham, R., Deckard, C., 2021. Non destructive evaluation methods for metal additive manufacturing. *Materials Evaluation*, 79(7), 931–946. <https://doi.org/10.32548/2021.me-13345>
- [10] Kakad, G.S., Gaddamwar, S.S., 2023. Optimizing heat exchanger design in the textile industry through additive manufacturing: An empirical study. *International Journal of Scientific Research in Science, Engineering and Technology*, 10(6), 387–396. <https://doi.org/10.32628/IJSRSET23106120>
- [11] Gibson, I., Rosen, D., Stucker, B., 2015. *Additive Manufacturing Technologies: 3D Printing, Rapid Prototyping, and Direct Digital Manufacturing*. Springer. <https://doi.org/10.1007/978-1-4939-2113-3>
- [12] Ngo, T.D., Kashani, A., Imbalzano, G., Nguyen, K.T.Q., Hui, D., 2018. Additive manufacturing (3D printing): A review of materials, methods, applications, and challenges. *Composites Part B: Engineering*, 143, 172–196. <https://doi.org/10.1016/j.compositesb.2018.02.012>
- [13] Gaddamwar, S.S., Shrekar, R.M., 2021. Investigation regarding solar chimney power plants by ET approach: A literature study. *International Journal of Scientific Research in Science and Technology*, 8(2), 693–698. <https://doi.org/10.32628/IJSRST2182123>
- [14] G. S. Kakad and S. S. Gaddamwar, “Advancements in textile engineering through additive manufacturing: Opportunities and challenges,” *International Journal of Scientific Research in Science and Technology*, 2023. <https://doi.org/10.32628/IJSRST>
- [15] S. S. Gaddamwar, R. M. Shrekar, and P. H. Bhagat, “Solar thermal driven high temperature heat exchanger technologies: A review with insights from high pressure gas cooling applications,” *International Journal on Recent and Innovation Trends in Computing and Communication*, vol. 11, no. 11. <https://ijritcc.org>
- [16] S. S. Gaddamwar, R. M. Shrekar, and N. P. Achmelwar, “Integrated thermal enhancement strategies for high temperature gas energy systems: Applications in solar thermal power and underground energy conversion,” *Journal of Computational Analysis and Applications*, vol. 33, no. 8, pp. 1–15, 2024. <https://doi.org/10.48047/jocaaa.2024.33.08.400>
- [17] S. S. Gaddamwar and R. M. Shrekar, “Advanced applications of additive manufacturing in the design and fabrication of high-performance aerospace heat exchangers,” *International Journal of Scientific Research in Engineering and Management*, vol. 9, no. 8, 2025. <https://ijsrem.com>
- [18] S. S. Gaddamwar and R. M. Shrekar, “Additive manufacturing applications in advanced heat exchangers for the aerospace industry,” *International Journal of Engineering Development and Research*, vol. 13, no. 3, pp. 47–51, 2025. <https://www.ijedr.org>
- [19] S. S. Gaddamwar and R. M. Shrekar, “Investigation regarding solar chimney power plants by ET approach: A literature study,” *International Journal of Scientific Research in Science and Technology*, vol. 8, no. 2, pp. 1–8, 2021. <https://doi.org/10.32628/IJSRST218397>
- [20] G. S. Kakad and S. S. Gaddamwar, “Advancing heat exchanger technology in textile engineering materials for electric vehicles through additive manufacturing,” *International Journal of Scientific Research in Mechanical and Materials Engineering*, 2024. <https://ijsrmm.com>
- [17] S. S. Gaddamwar, R. M. Shrekar, and P. H. Bhagat, “Review of augmented and membrane based heat exchanger technologies for high pressure gas applications in underground coal gasification and solar thermal systems,” *NeuroQuantology*, vol. 20, no. 8, pp. 11564–11568, 2022. <https://doi.org/10.48047/nq.2022.20.8.nq221197>
- [18] R. U. Sambhe and S. S. Gaddamwar, “Approximate representation and exposition of ISI flat plate collector including revised flat plate collector: A review,” *International Journal of Scientific Research in Science, Engineering and Technology*, vol. 7, no. 2, 2020. <https://doi.org/10.32628/IJSRSET207275>